

Application No.: 10/716,811

3

Docket No.: 275412001800

AMENDMENTS TO THE CLAIMS

Claim 1 (withdrawn): A photomask for use in photolithography-based production of a hologram element having a hologram which is divided into a plurality of regions in each of which a diffraction grating is formed, the photomask comprising:

a plurality of mask regions for forming the diffraction gratings of the respective regions of the hologram, the mask regions being composed of a non-light-transmitting mask portion and a light-transmitting portion,

wherein, of the plurality of mask regions, at least two mask regions are configured differently from each other in arrangement interval at which the light-transmitting portions are arranged in an alignment direction, and in ratio of an alignment-direction-wise width for the light-transmitting portions to the alignment-direction-wise arrangement interval for the light-transmitting portions.

Claim 2 (withdrawn): The photomask of claim 1, wherein the ratio of the alignment-direction-wise width to the alignment-direction-wise arrangement interval for the light-transmitting portions in a mask region having a shorter light-transmitting-portion arrangement interval is made smaller than the ratio of the alignment-direction-wise width to the alignment-direction-wise arrangement interval for the light-transmitting portions in a mask region having a longer light-transmitting-portion arrangement interval.

Claim 3 (withdrawn): The photomask of claim 1, wherein, in each of the regions, the ratio of the alignment-direction-wise width to the alignment-direction-wise arrangement interval for the light-transmitting portions is set at 0.5 or below.

pa-1027098

Application No.: 10/716,811

4

Docket No.: 275412001800

Claim 4 (currently amended): A method for producing a hologram-element, comprising:
performing light exposure by a photolithography method in which ~~[[the]] a~~ photomask ~~of~~
~~claim 1~~ comprising:

a plurality of mask regions for forming diffraction gratings of respective regions of a
hologram, the mask regions being composed of a non-light-transmitting mask portion and a light-
transmitting portion,

wherein, of the plurality of mask regions, at least two mask regions are configured
differently from each other in arrangement interval at which the light-transmitting portions are
arranged in an alignment direction, and in ratio of an alignment-direction-wise width for the light-
transmitting portions to the alignment-direction-wise arrangement interval for the light-transmitting
portions, is used, with a light-exposure amount kept in a level where respective hologram regions
having diffraction gratings are equal in first-order diffraction efficiency.

Claim 5 (currently amended): A method for producing a hologram-element, comprising:
performing light exposure by a photolithography method ~~in which the photomask of claim 2~~
according to claim 4, wherein in said photomask, the ratio of the alignment-direction-wise width to
the alignment-direction-wise arrangement interval for the light-transmitting portions in a mask
region of a shorter light-transmitting-portion arrangement interval is made smaller than the ratio of
the alignment-direction-wise width to the alignment-direction-wise arrangement interval for the
light-transmitting portions in a mask region having a longer light-transmitting-portion arrangement
interval is used, with a light-exposure amount kept in a level where respective hologram regions
having diffraction gratings are equal in first-order diffraction efficiency.

Claim 6 (currently amended): A method for producing a hologram-element, comprising:

pa-1027098

Application No.: 10/716,811

5

Docket No.: 275412001800

performing light exposure by a photolithography method ~~in which the photomask of claim 2~~
according to claim 4, wherein, in each of the regions of the photomask, the ratio of the alignment-
direction-wise width to the alignment-direction-wise arrangement interval for the light-transmitting
portions is set at 0.5 or below is used, with a light exposure amount kept in a level where respective
~~hologram regions having diffraction gratings are equal in first-order diffraction efficiency.~~

Claim 7 (currently amended): A method for producing a hologram-element, comprising:

performing light exposure by a photolithography method in which the ~~photomask of claim 1~~
a photomask of claim 1 comprising:

a plurality of mask regions for forming diffraction gratings of respective regions of a
hologram, the mask regions being composed of a non-light-transmitting mask portion and a light-
transmitting portion,

wherein, of the plurality of mask regions, at least two mask regions are configured
differently from each other in arrangement interval at which the light-transmitting portions are
arranged in an alignment direction, and in ratio of an alignment-direction-wise width for the light-
transmitting portions to the alignment-direction-wise arrangement interval for the light-transmitting
portions, is used, with a light-exposure amount kept in a level where a hologram region having a
diffraction grating with a shorter grating interval is made larger in first-order diffraction efficiency
than a hologram region having a diffraction grating with a longer grating interval.

Claim 8 (currently amended): A method for producing a hologram-element, comprising:

performing light exposure by a photolithography method ~~in which the photomask of claim 2~~
according to claim 7, wherein in said photomask, the ratio of the alignment-direction-wise width to
the alignment-direction-wise arrangement interval for the light-transmitting portions in a mask
region of a shorter light-transmitting-portion arrangement interval is made smaller than the ratio of

pa-1027098

Application No.: 10/716,811

6

Docket No.: 275412001800

~~the alignment-direction-wise width to the alignment-direction-wise arrangement interval for the light-transmitting portions in a mask region having a longer light-transmitting-portion arrangement interval is used, with a light exposure amount kept in a level where a hologram region having a diffraction grating with a shorter grating interval is made larger in first order diffraction efficiency than a hologram region having a diffraction grating with a longer grating interval.~~

Claim 9 (currently amended): A method for producing a hologram-element, comprising:
performing light exposure by a photolithography method according to claim 7, wherein, in each of the regions of the photomask, the ratio of the alignment-direction-wise width to the alignment-direction-wise arrangement interval for the light-transmitting portions is set at 0.5 or below in which the photomask of claim 3 is used, with a light exposure amount kept in a level where a hologram region having a diffraction grating with a shorter grating interval is made larger in first order diffraction efficiency than a hologram region having a diffraction grating with a longer grating interval.

Claim 10 (withdrawn): A hologram element comprising:
a hologram which is divided into a plurality of regions in each of which a diffraction grating is formed,

wherein, of the regions, at least two regions have different diffraction grating intervals and different duty ratios, the duty ratio referring to a ratio of an alignment-direction-wise groove opening width to the grating interval in the diffraction grating.

Claim 11 (withdrawn): The hologram element of claim 10, wherein a duty ratio of the diffraction grating having the maximum grating interval is set at 0.5 or below, whereas a duty ratio of the diffraction grating having the minimum grating interval is set at 0.5 or above, the duty ratio

pa-1027098

Application No.: 10/716,811

7

Docket No.: 275412001800

referring to a ratio of the alignment-direction-wise groove opening width to the grating interval in the diffraction grating.

Claim 12 (withdrawn): A hologram element comprising:

a hologram which is divided into a plurality of regions in each of which a diffraction grating is formed,

wherein, of the regions, at least two regions differ in diffraction grating interval, but are equal in first-order diffraction efficiency.

Claim 13 (withdrawn): A hologram element comprising:

a hologram which is divided into a plurality of regions in each of which a diffraction grating is formed,

wherein, of the regions, at least two regions have different diffraction grating intervals,

and wherein the regions of the hologram are equal to each other in first-order diffraction efficiency in a state of being coated with a reflection preventive film.

Claim 14 (new): A method for producing a hologram-element, comprising:

performing light exposure using a photomask comprising a hologram, wherein the hologram is divided into a plurality of regions in each of which a diffraction grating is formed, wherein, of the regions, at least two regions have different diffraction grating intervals, and wherein the regions of the hologram are equal to each other in first-order diffraction efficiency in a state of being coated with a reflection preventive film.

Claim 15 (new): A hologram element formed by a method according to claim 14.

pa-1027098

Application No.: 10/716,811

8

Docket No.: 275412001800

Claim 16 (new): A hologram element formed by a method according to claim 4.

Claim 17 (new): A hologram element formed by a method according to claim 4, wherein a duty ratio of the diffraction grating having the maximum grating interval is set at 0.5 or below, whereas a duty ratio of the diffraction grating having the minimum grating interval is set at 0.5 or above, the duty ratio referring to a ratio of the alignment-direction-wise groove opening width to the grating interval in the diffraction grating.

Claim 18 (new): A hologram element formed by a method according to claim 4, wherein, at least two of the regions differ in diffraction grating interval, but are equal in first-order diffraction efficiency.

pa-1027098